



opam **command** --help show the manpage for *command*
 Non-ambiguous prefixes are accepted
 (e.g. opam **inst** . --deps for opam **install** . --deps-only).

Installation

Download from: <https://opam.ocaml.org>

opam **init** set up opam , default repository, switch, scripts
 opam **init** --bare create ~/.opam without a compiler switch
 opam **init** --reinit -i reinstall opam scripts (e.g. after upgrade)

Run `eval $(opam env)` when changing switch or prompted, or accept the shell hook setup.

Configuration

opam **config report** display a summary of the set-up
 opam **command** -v[v] print commands being run
 opam **config set** v val set switch variable v
 opam **config set-global** v val set global config variable v
 opam **command** --root root run opam using root as opam root
 opam **command** --switch sw run opam on given sw
 opam **clean** remove archive cache and artefacts

Switches

opam **switch create** [name] compiler
 install a new prefix (“switch”) with the given *compiler* and select it.
compiler should be one of `ocaml-base-compiler[.version]`,
`ocaml-system[.version]`, `ocaml-variants[.version]`, or --empty.
 opam **switch** list installed switches
 opam **switch sw** select the switch sw
 opam **switch create dir** [compiler] install packages defined in *dir* in a
 new local switch
 opam **switch list-available** list all available compilers
 opam **exec** [--switch sw] -- command args
 run *command args* in the correct environment

The “current switch” is defined by the OPAMSWITCH environment variable, the PWD (for local switches), and the latest selected one.

Allowed URL formats

http:// https:// ftp:// remote archives
 ssh:// file:// archives or directories
 path file paths (version control is detected)
 user@host:path ssh addresses (using *rsync*)
 git:// hg:// darcs:// version control
 git+ssh:// hg+https:// git+file://
 version control with specific transport
 git+https://foo.com/git/bar#branch
 specific tag, branch, commit, etc.

Packages

opam **install** pkgs
pkgs are package names, *pkg.version*, constraints "*pkg>=version*"
 opam **install** --show only print a list of actions
 opam **install** --dry-run simulate everything
 opam **install** pkgs --best-effort
 don't fail on impossible requests
 opam **update** [--all] update repositories and package sources
 opam **upgrade** [pkgs] bring installed packages to latest version
 opam **remove** pkgs uninstall packages
 opam **remove** --auto uninstall no longer needed dependencies
 opam **reinstall** pkgs recompile and reinstall packages
 opam **source** pkg [--dev] download package source
 opam **reinstall** --list-pending
 show pending recom compilations
 opam **reinstall** --forget-pending
 at your own risk

Exploring

opam **list** list installed packages
 opam **list** --resolve pkg list a *sufficient* set of
 dependencies to install *pkg*
 opam **list** [--rec] --required-by pkg list dependencies of *pkg*
 opam **list** [--rec] --depends-on pkg list packages depending on *pkg*
 opam **list** --roots exclude automatically-installed
 dependencies
 opam **list** --external pkg list external *pkg* dependencies
 opam **list** --owns-file file find package owning *file*
 opam **show** pkg [--field=flds] show package details
 opam **show** pkg --raw show package opam file
 opam **show** pkg --list-files list all files belonging to *pkg*
 opam **var** v print value of opam variable
 opam **config list** [pkg] list variables [of package *pkg*]

Package pinning

opam **install** dir pin and install packages from the sources and
 definitions at *dir*
 opam **pin** pkg version pin *pkg* to given version
 opam **pin** pkg[.version] url pin *pkg*¹ to *url* (can be a dir) and install
 opam **pin** url pin using package definitions at *url*
 opam **pin** --dev pkg pin known package to its source repo
 opam **pin** [--short] list pinned packages
 opam **pin remove** pkgs|dir unpin packages
 opam **pin edit** pkg tweak package definition

pin commands also install/remove unless -n is specified.

¹If not using *pkg.version*, version is defined by opam file, directory name, or latest known version.

Project development

Working with local pins

opam **install** pkg|dir --deps-only
 just install all the pre-requisites
 opam **install** pkg|dir --working-dir
 bypass VCS, take all uncommitted changes
 opam **install** pkg|dir --inplace-build
 process build and install directly in the source
 opam **install** pkg|dir --assume-built
 directly run install commands from the source
 opam **lint** pkg|dir|opamfile
 check the style of a package definition

Sharing a dev setup

opam **lock** pkg --direct-only
 generate an opam.locked file with version-strict dependencies
 opam **lock** pkg
 generate an opam.locked file with a fixed dependency tree
 opam **install** dir|pkg --locked
 install, reproducing the same state as described by the locked file
 opam **switch export|import** file|-
 switch state (compiler, installed packages, pins...) save/restore

Configuring remotes

opam **repository** [--all]
 list defined repositories (current switch, or all)
 opam **switch create** --repos default,custom=url ...
 create a switch with repositories default, and newly defined custom
 opam **repository add** name url --dont-select
 define repository *name* at *url*
 opam **repository add** name [url]
 use *name* in the current switch
 opam **repository add** name [url] --set-default
 use *name* for newly created switches
 opam **repository add** name [url] --all-switches
 use *name* for all existing switches
 opam **repository add** name [url] --rank=-1
 use *name* with lowest priority
 opam **repository set-url** name url
 change repository url
 opam **repository set-repos** foo,bar
 redefine the repos selections for the current switch

The definition for *pkg.version* is taken from the highest ranking repository.



Package definition files

Full specification: <http://opam.ocaml.org/doc/Manual.html#opam>

In source: opam, or *pkg*.opam, or opam/*pkg*.opam

In a package repository: packages/*pkg*/*pkg.version*/opam

```

opam-version: "2.0"
name: "project"
version: "0.1"
synopsis: "One-line description"
description: ""
  Longer description
  ""
maintainer: "Name <email>"
authors: ["Name <email>"]
license: "SPDX license" # see https://spdx.org/licenses/
homepage: "https://project.org"
bug-reports: "https://gitfoo.net/project/issues"
dev-repo: "git+https://gitfoo.net/project.git"
depends: ["ocaml"
  "ocamlfind" {<= "1.8"}
  "odoc" {with-doc & >= "1.0"}]
# with a regular ./configure - make
build: [["./configure" "--prefix=%{prefix}%"]
  [make]]
install: [make "install"]
# with dune (no 'install:' needed)
depends: ["dune" {>= "1.10"}] # add to your other 'depends:'
build: ["dune" "build" "-p" name "-j" jobs]

```

External dependencies

name: "conf-gtk3" by convention, use a "conf-" prefix

depexts: ["libgtk-3-dev"] {os-family = "debian"}
define system package dependencies

flags: conf package without install, for polling the system

Related commands:

opam **list** -e --resolve *pkg* print requirements of *pkg* on this system

opam **depext** *pkg* handles requirements of *pkg* (plugin)

Some optional fields

```

tags: ["org:foo" "examples"] for package sorting
depopts: [deps] optional dependencies
substs: ["foo"] expand file "foo" from "foo.in"
patches: ["f.patch" {os = "macos"}]
  conditional patches
run-test: [cmds] only when running with --with-test
pin-depends: [["pkg.version" "url"]]
  when pinned, pin also these
conflicts: [deps] anti-dependencies
available: condition pre-requirements
build-env: [CC = "foo"] custom build/install environment
extra-source "fname" {src: "url" checksum: "sha256=..."}
  additional downloads
post-messages: "" "message" "" {condition}
  print to the user after install

```

When in a repository (not in-source):

```

url {
  src: "url" archive URL (or VCS, in custom repos)
  checksum: "sha512=XXX" supported: md5, sha256, sha512
}

```

Publishing

Through Github pull-requests to the official repository at

<https://github.com/ocaml/opam-repository>

Automatically, using the opam-publish plugin:

opam **publish** *url* publish from hosted source archive (plugin)

opam **publish** [*dir*] publish latest tag from detected Github origin

Expressions

Variables are strings, booleans or undefined values.

```

postfix conditions [make "opt" {condition} "foo" ] {condition}
dependencies ("p1" {>= "0.5" & != "0.7" & condition} | "p2")
version ordering "1.02" = "1.2" < "1.12" < "2.0~" < "2.0"
comparisons var = "value", var != "", "0.1" <= var
interpolation "can be %{var}% or %{bool-var?foo:bar}%"
undefined (?undef) is false, (undef | true) is true

```

`_:var` is *pkg:var* for the current package

Some useful variables:

Strings

name, *version* current package name, version
allowed e.g. as **depends**: ["foo" {= *version*}]

lib this is "%{prefix}%/lib"

pkg:lib this is "%{prefix}%/pkg/lib"

arch, *os*, *os-distribution*, *os-family*, *os-version*
system detection

Booleans

pkg:dev *pkg* was not built from a release archive

with-test tests have been enabled (package-specific)

with-doc documentation has been enabled (package-specific)

build (only in depends) don't recompile when changed

post (only in depends) not needed at build time

Run opam **var** for more

Repository administration

To be run from the root of an opam repository:

opam **admin list** list packages

opam **admin cache** download all archives to cache

opam **admin index** generate an index (needed for HTTP)

opam **admin lint** lint all packages

opam **admin filter patterns** only keep matching packages

opam **admin add-constraint** "*pkg*<=3"

add a version constraint to all dependencies towards *pkg*